

# **High Power LED Flood Light Fixture**

Date \_

FLC-x50W

Project Name \_\_\_\_\_

Type \_

## Flood Light Compact Series

#### **Compact Flood Lights**

Compact LED flood lights emit wide beam angles of powerful illumination for landscape lighting, parking lot lighting, tree uplighting, flagpole lighting, and architectural wall washing. Wattages range from 10 to 100—significantly less than 100- to 400-watt metal-halide (MH) flood lights with comparable light output. Each weatherproof LED fixture is constructed of heavy-duty materials with an integral heat sink and a built-in UL-Recognized Mean Well constant-current driver. Adjustable mounting brackets allow for direct illumination where it's needed. These LED flood lights are designed to last up to 30,000 hours—3 times longer than MH fixtures.

#### **Specifications**

FLC-CW10W			
Intensity	800 lumen		
Operating Voltage Range	110-240 VAC		
Beam Angle	120 degree		
Comparable MH Wattage	80-90 Watts		
LED Brand	Phillips		
Number of LEDs	10 LEDs		
Operating Temperature	-20~45 °C		
Color Temperature	5200K		
CRI	85		
IP Rating	IP65		
Total Power Consumption	10 Watts		
LED Lifetime	30000 Hours		
Warranty	5 Years		

FLC-CW20W				
Intensity	1700 lumen			
Operating Voltage Range	100~240 VAC			
Beam Angle	120 degree			
Comparable MH Wattage	160-170 watts			
LED Brand	Phillips			
Number of LEDs	20 LEDs			
Operating Temperature	-20~45 °C			
Color Temperature	5100K			
CRI	82			
IP Rating	IP65			
Total Power Consumption	20 Watts			
LED Lifetime	30000 Hours			
Warranty	5 Years			



FLC-CW50W		
Intensity	3400 lumen	
Operating Voltage Range	100~295 VAC	
Beam Angle	120 degree	
Comparable MH Wattage	345 watts	
LED Brand	Phillips	
Number of LEDs	50 LEDs	
Operating Temperature	-20~45 °C	
Color Temperature	3000K/5000K	
CRI	80 / 82	
IP Rating	IP65	
Total Power Consumption	50 Watts	
LED Lifetime	30000 Hours	
Warranty	5 Years	

FLC-CW70W			
Intensity	6400 lumen		
Operating Voltage Range	100~295 VAC		
Beam Angle	120 degree		
Comparable MH Wattage	640 watts		
LED Brand	Samsung		
Number of LEDs	70 LEDs		
Operating Temperature	-20~45 °C		
Color Temperature	5100K		
CRI	82		
IP Rating	IP65		
Total Power Consumption	72Watts		
LED Lifetime	30000 Hours		
Warranty	5 Years		

FLC-CW100W			
Intensity	9000 lumen		
Operating Voltage Range	100~295 VAC		
Beam Angle	120 degree		
Comparable MH Wattage	905 watts		
LED Brand	Phillips		
Number of LEDs	100 LEDs		
Operating Temperature	-20~45 °C		
Color Temperature	5100K		
CRI	84		
IP Rating	IP65		
Total Power Consumption	104Watts		
LED Lifetime	30000 Hours		
Warranty	5 Years		

# FLC-CW10W



FLC-CW20W



FLC-x70W / FLC-CW70W-DM



MS-200



FLC-CW30W



FLC-CW100W



**POWERCORD** 





### **Ordering Information**

LED Product	Color Temperature	Wattage	Quality
FLC - Flood Light Compact	CW - Cool White	<b>10W</b> - 10 watts	N/A
		<b>20W</b> - 20 watts	N/A
		<b>30W</b> - 30 watts	N/A
		<b>50W</b> - 50 watts	N/A
		<b>70W</b> - 70 watts	DM - Cosmetic Blemish
		<b>100W</b> - 100 watts	N/A







Rev Date: V1 02/29/2016





**LED Product Accessory** 

WPTB-3 - Waterproof Wire Terminal Block MS-200 - Ground Mounting Stake 200mm **POWERCORD** - Power Cord for Power Supplies



### **Dimensional Drawings**





FLC-CW20W










### **Dimensional Drawings**











### **Dimensional Drawings**

