

GBL Series

LED Gooseneck Sign Light Specifications

Project _____

Date _____ Type _____



Description

GBL series gooseneck sign lights are a combination of classic architectural style and reliable LED performance. Wall mount fixture design illuminates signs, awnings, storefronts, and more. Angled shade casts a controlled flood beam that is directed down or toward the surface it's attached to, adjusted with the swivel head. The die cast aluminum housing comes in various finishes to compliment a variety of spaces and resist corrosion. Integrated LEDs keep out bugs and debris and eliminate the need for bulb replacement. Though durable enough to withstand outdoor installation for signage, the sleek modern design can also be used in interior locations such as restaurant menu boards or wall artwork.

Mechanical

- Wall mount to junction box with integral bracket
- Swivel knuckle allows angle adjustment up to 180°
- Available in black, architectural bronze, or white finish
- Die cast aluminum housing with polycarbonate lens
- Gasketed enclosure
- Gooseneck arm design and 10 in. angled dome shade
- Operating temperature of -22°-122° F (-30°-50° C)
- IP65 rated for wet conditions

Electrical

- 120-277 VAC input
- 20 W
- 0-10 V dimmable
- 50,000 hour (L70 rated) lifespan
- 20 AWG wiring

Photometrics

- 100° beam angle
- 2,400 lumens / 120 lm/W
- 80+ CRI 4000K light

Available Models¹

- GBL-40K20T8-L15SLBK
- GBL-40K20T8-L15SLBR
- GBL-40K20T8-L15SLWH

Part Number Breakdown

Example: GBL-40K20T8-L15SLBK

Family	Color Temperature	Wattage	Design	Finish
GBL	40K [4000K]	20T8 [20 W]	L15SL [gooseneck with sloped shade]	BK [black]
				BR [brown]
				WH [white]

Certifications and Compliances

These lights are UL Listed in compliance with UL 1598 (IFAM).




Application

Easily replace inefficient ? fixtures such as those used to light signs, advertisement and menu boards, artwork, awnings, and banners. These are a great solution for wall washing and work very well for storefronts, restaurants, and other areas where good lighting is needed to highlight information or the features of a retail space.

Warranty

Five (5) Year Warranty.

Beam Angle



T 866.811.5550
 F 314.972.6202
 email: commercial-sales@superbrightleds.com
 www.superbrightleds.com/cat/industrial-led-lighting/

¹Contact customer service if interested in options other than those listed.

Rev V1 Date: 7/19/2021


Specifications are subject to change without notice.

Printed in the U.S.A.

GBL Series

LED Gooseneck Sign Light Specifications

Dimensional Drawing



Specifications

Model	GBL-40K20T8-L15SLBK	GBL-40K20T8-L15SLBR	GBL-40K20T8-L15SLWH
Operating Voltage	120-277 VAC		
Power Consumption	20 W		
Current Draw	167 mA @ 120 VAC / 72 mA @ 277 VAC		
Intensity	2,400 lm		
Efficacy	120 lm/W		
Color Temperature	4000K		
Beam Angle	100°		
CRI	80+		
Dimming	0-10 V		
IP Rating	IP65		
Ambient Operating Temperature	-22°-122° F (-30°-50° C)		
Product Weight	3.3 lb (1.5 kg)		
Rated Life (L70)	50,000 hours		
Finish	black (RAL 9017)	architectural bronze (Pantone 412C)	white (RAL 9016)

