

**Important: Read all instructions prior to installation.**

## Mini Emergency LED Light Bar

### Safety and Notes

- Avoid looking directly into lamp when illuminated.
- Do not mount upside down or in enclosed space.
- Do not submerge in water or expose to high pressure jets of water or steam when cleaning.
- Not intended for use while vehicle is traveling faster than parking lot speeds (approximately 15–20 MPH).



### Specifications

Model	STMB-AW48-MB
Voltage	12-24 VDC
Wattage	48 W
Current Draw	4 A @ 12 VDC
IP Rating	IP66
Wire Length	9.5 ft (2.9 m)
Operating Temperature	-22°–140° F (-30°–60° C)

### Operation

Switch	Operation
ON / OFF	turns power on or off
Pattern Select	press for 1 second or less for next pattern
	hold for 1–3 seconds for the previous pattern
	hold for 3–5 seconds to return to pattern 1
	hold for 5–10 seconds to place light in standby mode

### Flash Patterns

Pattern	Pattern Name	Pattern	Pattern Name
1	Single	14	CCW Constant Flash
2	Double	15	CW Single
3	Half / Half	16	CCW Single
4	Cross Flash	17	CW Rotation
5	CW Rotation	18	CCW Rotation
6	CCW Rotation	19	CCW-CW
7	All-Half	20	Single - Slow
8	All-Single Quick	21	Double - CW Single
9	Triple	22	Single Alternate
10	Quad	23	Quint Alternate
11	Eight Flash	24	Half Steady Half Single
12	Twelve Flash	25	Half Steady Half Single
13	CW Constant Flash	26	Steady On