

Light efficiency:

142 Lumen/Watt

Output: 28517 lm

Light quality:

CRI: 85.2


Peak: 9754 cd

Color temperature:

5336 K

Power: 200.4 W

PF: 1.0



Product name:

UHBD2-50K200H-110

Date and time:

5/27/2020 2:19:42 PM

Beam angle

116.4°




CIE 1931


x: 0.336

y: 0.341

Spectra



Power





T 314.743.3067

F 314.972.6202


email: commercial-sales@superbrightleds.com

www.superbrightleds.com/


Color Specifications



TM30: 82.3



CRI: 85.2 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
84.7	90.1	92.7	85.7	85.3	84.9	87.2	71.0	17.9	75.6	85.7	65.7	86.2	96.2	80.1


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
75.3	82.9	77.5	85.3	87.2	93.8	91.8	86.8	84.0	73.1	71.4	87.6	85.8	83.9	73.6	80.1

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
84.6	97.5	75.5	72.7	80.5	84.6	87.5	90.5	95.9	85.0	80.6	79.2	80.0	72.4	77.0

CQS: 81.4



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
5336 K	85.2	17.9	82.3	96.2	81.4	0.336	0.341	0.210	0.319	-0.0052



TM30 Report







Rf 82.3

Fidelity index Rf


Rg 96.2

Gammut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	75	-12%	0%
2	83	-7%	6%
3	77	-4%	11%
4	85	0%	7%
5	87	1%	4%
6	94	2%	-1%
7	92	-3%	-2%
8	87	-7%	1%
9	84	-8%	9%
10	73	-5%	14%
11	71	2%	16%
12	88	5%	5%
13	86	9%	-4%
14	84	4%	-7%
15	74	0%	-18%
16	80	-3%	-11%



Illumination



Beam intensities from 1-20m


1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
9744lx	2436lx	1083lx	609lx	390lx	271lx	199lx	152lx	120lx	97lx	81lx	68lx	58lx	50lx	43lx	38lx	34lx	30lx	27lx	24lx
905.2fc	226.3fc	100.6fc	56.6fcd	36.2fcd	25.1fcd	18.5fcd	14.1fcd	11.2fcd	9.1fcd	7.5fcd	6.3fcd	5.4fcd	4.6fcd	4fcd	3.5fcd	3.1fcd	2.8fcd	2.5fcd	2.3fcd

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
116.4°	154.7°	165.5°	81.1%	54.5%



ISO Diagrams

ISO candela diagram




10%	974 cd
20%	1949 cd
30%	2923 cd
40%	3898 cd
50%	4872 cd
60%	5846 cd
70%	6821 cd
80%	7795 cd
90%	8770 cd

Conditions:

Number of c-planes: 16

Candela at center: 9744 cd

ISO lux diagram



3%	2.92 lx
5%	4.87 lx
10%	9.74 lx
30%	29.2 lx
50%	48.7 lx

Conditions:

Number of c-planes: 16

Lux at center: 97.4 lx

Lux distribution on a surface when lamp is mounted at 10 meters from the surface.




Light Planning

Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	101	101	101	99
1	109	105	101	97	107	102	99	95	98	95	92	94	92	89	90	88	87	85
2	99	92	85	79	97	90	84	78	86	81	76	83	78	75	80	76	73	71
3	91	80	72	66	88	79	71	65	76	69	64	73	67	63	70	66	62	60
4	83	71	62	56	81	70	62	55	67	60	55	65	59	54	63	57	53	51
5	76	63	55	48	74	62	54	48	60	53	47	58	52	46	56	50	46	44
6	70	57	48	42	68	56	48	42	54	47	41	52	46	41	51	45	40	38
7	65	52	43	37	63	51	42	37	49	42	36	48	41	36	46	40	36	34
8	61	47	39	33	59	46	38	33	45	38	32	44	37	32	42	36	32	30
9	57	43	35	29	55	42	35	29	41	34	29	40	34	29	39	33	29	27
10	53	40	32	27	52	39	32	26	38	31	26	37	31	26	36	30	26	24

LAMPS (number of lamps)

Luminaire budgetary diagram



Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
924 lm	2676 lm	4127 lm	5090 lm	5410 lm	4891 lm	3516 lm	1532 lm	171 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
17.8 lm	23.5 lm	27.7 lm	27.5 lm	25.3 lm	22.6 lm	18.3 lm	12.1 lm	4.22 lm




Road Report

LCS table


BUG rating:	B4 U3 G3	
Forward light	Lumens	Lumens %
Low(0-30):	3864.6	13.6%
Medium(30-60):	7703	27%
High(60-80):	2549.7	8.9%
Very high(80-90):	96.8	0.3%
Back light		
Low(0-30):	3860.6	13.5%
Medium(30-60):	7676.8	26.9%
High(60-80):	2498.4	8.8%
Very high(80-90):	88.2	0.3%
Uplight		
Low(90-100):	18.1	0.1%
High(100-180):	161.1	0.6%

LCS graph



Stabilization

Warmup curve



Warmup result

Warmup time:	25 min 47 sec
Warmup variation	-5.7%

Warmup conditions

Stable period:	15 min
Stable change max:	2.0%
Minimum time:	15 min

Color temperature change

CCT start	CCT change	CCT end
5192 K	+144 K	5336 K

Output change

Output start	Output change	Output end
30213 lm	-1697 lm	28517 lm




Flicker


Flicker curve (complete sampled flicker signal)



Flicker frame (frame of one flicker period)



Flicker FFT (frequency scope of flicker curve)



Flicker results:

Flicker frequency:	118.69 Hz
Flicker index:	0.01
Flicker percentage:	2.22 %
SVM: (Visual flicker)	0.08

Flicker conditions:

Sample rate:	40000 samples/second
--------------	----------------------

